

TegraBond Penetrating Sealer

System	Suitable as consolidating treatment for various systems
Product Code	WB115PP
Product Description	A water based, low odour, single pack penetrating sealer specially formulated to bind and seal porous and powdery substrates.
Main Uses	TegraBond Penetrating Sealer is typically used over filler, plaster, bare faced render or concrete. Please refer to Integra Coatings Technical Services for advice on substrate preparation prior to priming.
Pack Size	5 litres
Coverage Rat	30 m ² /litre on smooth surfaces
Colour Range	Clear
Application	Brush or short/medium pile roller. Do not apply or allow to dry at temperatures below 5°C or if condensation is likely to occur.
Mix Ratio	As supplied
Pot life	N/A
Drying Time	1 hour @ 20°C <i>Note: Drying times will be shortened by higher and lengthened by lower temperatures</i>
Over coating Interval	Minimum: 2 hours, Maximum: 21 days
Flash Point	Above 32°C
Storage	Store at temperatures between 5°C and 25°C. Protect from frost.
Shelf life	6 months in original unopened containers
Health & Safety	Refer to current copy of Health and Safety Data Sheet
Disclaimer	<i>The information given above is true and accurate to the best of our knowledge and is given in good faith but without any warranty. Please ensure you are reading a current and updated copy of this data sheet Integra Coatings Limited will not accept any claim for consequential or incidental damages.</i>