

TegraShield Class “0” Colour Coat

System	TegraShield Class “0” Barrier System
Product Code	WB142FR
Product Description	A water-based, low odour, single pack, pigmented resin system, containing inorganic extenders and flame retardants.
Key System Benefits	The TegraShield Class “0” Barrier System successfully upgrades the worst case scenario Warrington “Blue” Board to Class 1 and 0. Overcoating very high risk flammable multi-layered paints is therefore a safe and secure option.
Main Uses	The TegraShield Class “0” Barrier System has been designed to protect highly flammable paint layers on communal area walls and ceilings from uncontrolled flame spread. Typically high rise, low rise, sheltered housing, schools and hospitals all benefit from TegraShield protection.
Pack Size	5 Litres
Coverage Rate	6-12 m ² /litre
Colour Range	BS4800, RAL, NCS or colour matching on request
Application	Brush or roller. Do not apply or allow to dry at temperatures below 5°C or if condensation is likely to occur.
Mix Ratio	Single Pack
Pot life	Not applicable
Drying Time	2 hours @ 20°C <i>Note:</i> Drying times will be shortened by higher and lengthened by lower temperatures
Overcoating Interval	Minimum: 24 hours, Maximum: 21 days
Flash Point	Non-flammable
Storage	Store at temperatures between 5°C and 25°C. Protect from frost.
Shelf life	6 months in original unopened packaging
Health & Safety	Refer to current copy of Health and Safety Data Sheet
Disclaimer	<i>The information given above is true and accurate to the best of our knowledge and is given in good faith but without any warranty. Please ensure you are reading a current and updated copy of this data sheet Integra Coatings Limited will not accept any claim for consequential or incidental damages.</i>