

TegraShield Class “0” Anti-Graffiti Lacquer

System	TegraShield Class “0” Barrier System
Product Code	WB143FR
Product Description	A high solids, twin-pack modified resin system specially formulated to provide a graffiti resistant surface.
Key System Benefits	The TegraShield Class “0” Barrier System successfully upgrades the worst case scenario Warrington “Blue” Board to Class 1 and 0. Overcoating very high risk flammable multi-layered paints is therefore a safe and secure option.
Main Uses	The TegraShield Class “0” Barrier System has been designed to protect highly flammable paint layers on communal area walls and ceilings from uncontrolled flame spread. Typically high rise, low rise, sheltered housing, schools and hospitals all benefit from TegraShield protection.
Pack Size	5 Litres
Coverage Rate	12-15 m ² /litre
Colour Range	Clear / Pigmented
Application	Brush or roller. Do not apply or allow to dry at temperatures below 5°C or if condensation is likely to occur.
Mix Ratio	Supplied in correct proportions. See container labels for detailed mixing instructions. Do not part mix.
Pot life	4 hours @ 20°C
Drying Time	6 hours @ 20°C <i>Note: Drying times will be shortened by higher and lengthened by lower temperatures</i>
Overcoating Interval	Minimum: 24 hours, Maximum: 21 days
Flash Point	Above 32°C
Storage	Store at temperatures between 5°C and 25°C. Protect from frost.
Shelf life	6 months in original unopened packaging
Health & Safety	Refer to current copy of Health and Safety Data Sheet
Disclaimer	<i>The information given above is true and accurate to the best of our knowledge and is given in good faith but without any warranty. Please ensure you are reading a current and updated copy of this data sheet Integra Coatings Limited will not accept any claim for consequential or incidental damages.</i>