

TegraBond APS Primer

System	Suitable as the foundation layer for various systems
Product Code	WB300APS
Product Description	A water based, low odour, single pack primer specially formulated to act as an adhesion promoter when overcoating stripped masonry substrates.
Main Uses	TegraBond APS Primer is typically used over old plaster and concrete that has been exposed by chemical or mechanical paint stripping. Please refer to Integra Coatings Technical Services for advice on substrate preparation prior to priming.
Pack Size	5 litres
Coverage Rate	12-14 m ² /litre on smooth plaster surfaces
Colour Range	White
Application	Brush or short/medium pile roller. Do not apply or allow to dry at temperatures below 3°C or if condensation is likely to occur.
Mix Ratio	As supplied
Pot life	N/A
Drying Time	2 hours @ 20°C <i>Note:</i> Drying times will be shortened by higher and lengthened by lower temperatures
Overcoating Interval	Minimum: 24 hours, Maximum: 21 days
Flash Point	Above 32°C
Storage	Store at temperatures between 5°C and 25°C. Protect from frost.
Shelf life	6 months in original unopened containers
Health & Safety	Refer to current copy of Health and Safety Data Sheet
Disclaimer	<i>The information given above is true and accurate to the best of our knowledge and is given in good faith but without any warranty. Please ensure you are reading a current and updated copy of this data sheet Integra Coatings Limited will not accept any claim for consequential or incidental damages.</i>